

HP 550 Notebook PC (FU411EA)



Fast facts

Processor type	Intel® Core™2 Duo Processor T5470 • 1.60 GHz, 2 MB L2 cache, 800 MHz FSB
Operating system installed	FreeDOS
Display type	TFT
Display size	15.4 inches diagonal
Product weight	Starting at 2.5 kg
Product dimensions (W x D x H)	3.2 (at front) x 35.8 x 26.7 cm
Battery life	Up to 4h30m

System features

Internal drives	250 GB
Hard disk drive speed	5400 rpm
Optical drives	DVD+/-RW SuperMulti DL LightScribe
Standard memory	1 x 2048 MB DDR2
Memory slots	2 SODIMM slots supporting dual channel memory
Memory upgrade	Upgradeable to 4096 MB maximum
Chipset	Mobile™ Intel® GME965

Portability

Product weight	Starting at 2.5 kg
Product dimensions (W x D x H)	3.2 (at front) x 35.8 x 26.7 cm

Display type	TFT
Display size	15.4 inches diagonal
Connectivity	
Wireless technologies	Intel a/b/g, Broadcom 802.11 b/g
Wireless capability	Yes
Modem	56K modem
Network interface	Intel Fast Ethernet Integrated Controller (10/100 NIC)
Expandability	
Expansion slots	Slots available for additional devices: 1 ExpressCard/54 slot, Secure Digital (SD) slot
External I/O ports	3 USB 2.0 ports, VGA, stereo microphone in, stereo headphone/line out, power connector, RJ-11, RJ-45
Software	
Pre-installed software	Preloaded software: HP Recovery Manager, Roxio Creator Basic 9
Graphic / audio	
Graphic subsystem name	Intel® Graphics Media Accelerator X3100
Graphic subsystem video card memory	Up to 384 MB shared system memory
Video resolutions description	1280 x 800 WXGA BrightView
Audio	High Definition Audio, mono speaker, stereo headphone/line out, stereo microphone in
Other information	
Keyboard	Full-sized keyboard
Pointing device	Touchpad with scroll zone
Power features	6-cell (47 WHr) Lithium-Ion battery
Power requirements	External 65W AC adapter, HP Fast Charge Technology
Battery life	Up to 4h30m
Security management	Device Access Manager for HP ProtectTools, Kensington Lock Slot
Operating temperature range	0 to 35° C
Non-operating humidity	5 to 95% RH
Storage temperature range (Celsius)	-20° to 60° C
Operating humidity range	10 to 90% RH